

In the claims:

All of the claims standing for examination are reproduced below.

1. (Previously presented) A security method using information transmission by light means between a user electronic apparatus having at least one input interface and a screen, and an electronic security device which comprises:

- a receive interface having at least one light sensor for receiving input information coming from the user electronic apparatus;
- an emit interface adapted to emit output information as a function at least of received input information, the output information corresponding to a security code for communicating to the input interface of the user electronic apparatus; and
- an electronic central unit connected to the receive and emit interfaces and adapted to determine the output information as a function at least of the input information and to cause said output information to be emitted by the emit interface; the security method comprising the following steps:
 - a) causing the input information to be transmitted by the user electronic apparatus to the receive interface of the electronic security device;
 - b) causing the output information to be determined by the central unit of the electronic security device, as a function of the input information;
 - c) causing the emit interface of the electronic security device to emit the output information corresponding to said security code, and communicating said security code to the user electronic apparatus, via the input interface of said user electronic apparatus; and
 - d) verifying that the security code received by the user electronic apparatus is related to the input information by a predetermined relationship; wherein during step a), the light sensor of the electronic security device is placed facing the screen of the user electronic apparatus while said screen is caused to emit a modulated light signal carrying the input information.

2. (Previously presented) A method according to claim 1, in which during step d), certain operations performed by means of the user electronic apparatus are authorized or not authorized as a function of verifying the security code.

3. (Previously presented) A method according to claim 1, in which the electronic security device belongs to a medium carrying digital data and readable by the user electronic apparatus.

4. (Previously presented) A method according to claim 3, in which the data medium used is an optical disk having an annular data area surrounding a central portion carrying no digital data, which central portion includes the light sensor.

5. (Previously presented) A method according to claim 1, in which, during step a), said modulated light signal is emitted in a predetermined area belonging to the screen, and the light sensor of the data medium is placed in the immediate vicinity of said predetermined area.

6. (Previously presented) A method according to claim 5, in which, during step a), said predetermined area of the screen is indicated by at least one mark displayed by the screen.

7. (Previously presented) A method according to claim 1, in which, during step c), the output information is emitted by the electronic security device in the form of a sound signal.

8. (Previously presented) A method according to claim 7, in which the sound signal containing the output information is listened to by a human operator, which operator determines the security code as a function of the listened-to signal and communicates this security code to the user electronic apparatus via its input interface.

9. (Previously presented) A method according to claim 7, in which the sound signal containing the output information is received directly by the input interface of the user electronic apparatus.

10. (Previously presented) A method according to claim 7, in which the sound signal containing the output information is transmitted to a remote monitoring station which determines the security code as a function of said sound signal and transmits said security code to the input interface of the user electronic apparatus.

11. (Previously presented) A method according to claim 1, in which during step c), the output information is emitted by the electronic security device by being displayed on a display device.

12. (Previously presented) A method according to claim 1, in which encoded data is caused to be interchanged between a remote central station communicating with the user electronic apparatus and the central unit of the electronic security device via the emit and receive interfaces of said electronic security device.

13. (Previously presented) A method according to claim 1, in which the electronic security device stores a count of units of value, and the central unit of said electronic security device is adapted to cause said count of units of value to vary as a function of encoded data received and emitted by the central unit via the received and emit interface.

14. (Previously presented) A method according to claim 1, in which the electronic security device belongs to a portable digital data medium which can be read by the user electronic apparatus while said data medium is set in motion, the electronic security device storing at least one count of utilization units, and the central unit of said security device causing said count to vary as a function of the movements of the data medium as

detected by a motion sensor.

15. (Previously presented) A method according to claim 14, in which the utilization unit count is read by an external reader using a communication interface belonging to said security device.

16. (Previously presented) A method according to claim 1, including a step of activating at least certain functions of the electronic security device, during which step a predetermined access code is communicated to the central unit of said electronic security device.

17. (Previously presented) A method according to claim 16, in which, during the activation step, the access code is communicated to the central unit by means of a user-actuable input interface of the electronic security device.

18. (Previously presented) A method according to claim 16, in which, during the activation step, the access code is communicated to the central unit by positioning the light sensor of the electronic security device successively in register with a plurality of predetermined areas belonging to the screen of the user electronic apparatus, the various predetermined areas of the screen emitting respective different predetermined optical signals, each corresponding to a symbol displayed on the screen.

19. (Previously presented) A method according to claim 16, in which, in order to communicate the access code to the central unit of the electronic security device, the access code is initially communicated to the user electronic apparatus using the input interface of the user electronic apparatus, the light sensor of the electronic security device is placed facing the screen of the user electronic apparatus, and said screen is caused to emit a modulated light signal corresponding to said access code.

20. (Previously presented) A method according to claim 1, in which, during step b), the central unit of the electronic security device is caused to determine the output information as a function of the input information and a personal code previously communicated to said central unit by the user of the electronic security device.

21. (Previously presented) A method according to claim 20, in which, during step b), the personal code is communicated to the central unit of the electronic security device by means of a user-actuatable input interface of the electronic security device.

22. (Previously presented) A method according to claim 20, in which, during step b), the personal code is communicated to the electronic central unit by positioning the light sensor of the electronic security device successively in register with a plurality of predetermined areas belonging to the screen of the user electronic apparatus, these various predetermined areas of the screen emitting respective different predetermined light signals and each corresponding to a symbol displayed on the screen.

23. (Previously presented) A method according to claim 20, in which, during step b), to communicate the personal code to the central unit of the electronic security device, the personal code is initially communicated to the user electronic apparatus by using the input interface of said user electronic apparatus, the light sensor of the electronic security device is placed facing the screen of the electronic user apparatus, and said screen is caused to emit a modulated light signal corresponding to said personal code.

24. (Previously presented) A method according to claim 20, in which, during step d), a monetary operation is either authorized or not authorized.

25. (Previously presented) A method according to claim 20, in which the electronic security device stores at least one count of units of value, and during step d) an operation implying a change to said count of units of value is either authorized or not authorized.

26. (Previously presented) A method according to claim 25, in which, during step d), units are exchanged between the count of units of value in the electronic security device and a remote count of units managed by a remote apparatus connected by telecommunications means to the user electronic apparatus.

27. (Previously presented) A method according to claim 26, in which, during step d), after a count of units of value in the electronic security device has been modified, the output interface is caused to emit acknowledgment information, and the acknowledgment information is communicated to the user electronic apparatus via the input interface of said user electronic apparatus.

28. (Previously presented) A method according to claim 20, in which, during step a):

- the user is caused to select a screen area on the screen of the user electronic apparatus, and associated with predetermined visual signaling amongst a plurality of screen areas associated with different visual signaling, said screen areas emitting respective different modulated light signals carrying different input information;

- the light sensor of the electronic security device is placed facing the screen area selected by the user and the modulated light signal emitted by said screen area is picked up by means of said light sensor; and

during step d), the user's selection is confirmed as a function of verifying the security code received by the user electronic apparatus during step d) after modifying the count of units of value in the electronic security device.

29. (Previously presented) A method according to claim 28, in which, during step d), a count of votes is incremented corresponding to the selection made by the user during step a), and providing said selection is validated by verification of the security code.

30. (Previously presented) A method according to claim 28, in which the electronic

security device stores information specifying previous elections in which the user of the electronic security device has participated, said information being updated by means of input information during step a), and during step b) or c), normal operation of the electronic security device is inhibited if the input information received for a new vote indicates that the user has already voted in this election.

31. (Previously presented) A method according to claim 30, in which, during step d), the screen is caused to emit a modulated light signal carrying an acknowledgment signal confirming that the user's vote has been taken into account, and the participation information in the memory of the electronic security device is updated only when the light sensor of the electronic security device has received this acknowledgment signal.

32. (Previously presented) A method according to claim 28, in which the modulated light signals corresponding to different screen areas are modified in random manner after each vote cast by a user.

33. (Previously presented) A method according to claim 28, in which the different screen areas are juxtaposed on the screen of the user electronic apparatus.

34. (Previously presented) A method according to claim 1, in which the input information is transmitted between at least two emitting areas belonging to the screen of the user electronic apparatus and at least two light sensors belonging to the electronic security device.

35. (Previously presented) A method according to claim 34, in which the light signals received by the two light sensors are decoded by calculating a difference between said light signals.

36. (Previously presented) A method according to claim 35, in which a binary signal is

determined by comparing said difference with a threshold value, and then said binary signal is processed by median filtering.

37. (Previously presented) A method according to claim 35, in which a binary signal is determined by comparing said difference with a threshold value previously determined by causing a predetermined calibration signal to be transmitted between the emitting areas of the screen and the light sensors.

38. (Previously presented) A method according to claim 34, in which one of the emitting areas of the screen emits a modulated light signal, while the other of said emitting areas emits a constant light signal.

39. (Previously presented) An optical disk for implementing a method according to claim 1, the disk comprising an annular data area surrounding a central portion carrying no digital data, said optical disk being readable by a user electronic apparatus by means of a light beam reader, which user electronic apparatus further comprises at least one input interface and a light- emitting screen, said data medium including an electronic security device which comprises:

- a receive interface having at least one light sensor disposed in the central portion of the optical disk and adapted to receive input information coming from the screen of the user electronic apparatus;

- an emit interface adapted to emit output information as a function of received input information, the output information corresponding to a security code for communication to the input interface of the user electronic apparatus; and

- an electronic central unit connected to the receive and emit interfaces and adapted to determine the output information as a function of the input information and to cause said output information to be emitted by the emit interface.

40. (Previously presented) An optical disk according to claim 39, in which the security device further includes a motion sensor.